

6" & 9" Lids

Torque Specifications



6" LID—SOLID CONFIGURATION
(SANTOPRENE, VITON, EPDM GASKET)

40 FT
POUNDS W/
COMPATIBLE
LUBRICANT



6" LID—2" NPT PLUG WITH GREEN TAMPER SEAL
(SANTOPRENE, VITON, EPDM GASKET)

40 FT
POUNDS W/
COMPATIBLE
LUBRICANT



6" LID—2" MICRO POROUS VENT WITH RED TAMPER SEAL
(SANTOPRENE, VITON, EPDM GASKET)

40 FT
POUNDS W/
COMPATIBLE
LUBRICANT



9" LID—SOLID CONFIGURATION
(SPONGE RUBBER GASKET)

75 FT
POUNDS



9" LID—2" MICRO POROUS VENT WITH RED TAMPER SEAL
(SPONGE RUBBER GASKET)

75 FT
POUNDS

2" INSERT FITTING
(SANTOPRENE GASKET)

30 IN
POUNDS

IBC North America

4545 Clawson Tank Drive
Clarkston, MI 48310
USA

Phone: 248-625-8700
Fax: 248-625-3066
www.ibcna.com

For more information or to obtain IBC North America's most up to date torque specification sheet, please visit our web site at www.ibcna.com. Information contained here is subject to change without notice.